

## PRO-VAC B1191

### next generation vacuum bagging sealant tape

Low to medium temperature sealant tape

#### Description:

- Improved level of tack and hand ability
- Tape performs best at room temperature (+ 20 °C), if the tape is too cold the tack levels will be dramatically reduced
- Recommended for use in vacuum infusion, wet lay-up bagging and bag to bag (envelope bagging) processing
- Compatible with most vacuum films and tool surfaces but pre-production trials are advisable
- We recommend that the tape is removed from the mould at room temperature

#### Technical data:

Max use temperature	150 °C - bag to tool and bag to bag
Colour	Black
Standard roll size PRO-VAC B1191	3mm x 12mm x 15m
Standard packaging PRO-VAC B1191	22 rolls per box – 50 boxes per pallet



\*The tape is also available in grey, as a double strip profile and a bead in various diameters

#### Packaging and storage

Store in original and unopened packaging and protected from humidity  
 Store at a maximum temperature of 30°C in a ventilated environment  
 Material has a 12 month shelf life from date of manufacture  
 Store flat with a maximum of 5 boxes stacked



**HF Industri & Marine** ApS

HF Industri & Marine ApS Gotlandsvej 6 5700 Svendborg Denmark  
 Phone: +45 62 20 13 12 • Fax: +45 62 20 14 77 • info@hfmarine.dk • www.hfmarine.dk

All statements, technical information and recommendations, including storage, contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability of this particular purpose and shall assume all risk and liability in connection herewith.